

MOOD LINE 55/40 - *Partition solitary*

Cosy-soft or austere elegant

The highly sound-absorbing Mood Line solitaire partitions in the wall thickness 55 mm and alternatively 40 mm, unlike the system walls have no magnetic connectors. Equipped with a powder-coated flat base, the Mood Line solitaire partitions are versatile and can also be used as a single wall and individually designed. The walls are available in a height of up to 1800 mm, in 39 standard sizes and in addition individually made to measure. The design feature of the version with fully upholstered walls are rounded corners with a radius of 20 mm. These give the elements a cosy soft character and a harmonious overall picture. In the version with the profiles on the inside, the strict angular design of the elements determines the appearance. This objective-strict version, also available in both wall thicknesses (55 mm and 40 mm) offers a wide range of design options for colour and material selection. So the inside profile can be coated with the same colour, or regardless of the selected colour and fabric type of walls, with fabric. Elegant and extremely high quality, the version with inner profiles is available in powder coated RAL 7016 anthracite gray and RAL 9006 white aluminium.



Data Mood Line *Partition solitary*

Wall thickness 55 mm - alternatively 40 mm

With full upholstery or alternatively with inner profile

Highly sound-absorbing according to
DIN EN ISO 354

Filler B1 flame retardant according to
DIN 4102-1


Filler OEKO-TEX Standard 100

Organisable with hook-in elements

Optionally also with an acoustic filling made of pure
new sheep's wool - 100% sustainable

Partition walls incl. central stand plate with 8 mm
height

Detail view



Solitary fully upholstered



Solitary with organisational accessories



Solitary fully upholstered with quilting



Solitary with inner profile RAL



Solitary with inner fabric profile



Solitary with inner fabric profile

Best acoustic qualities thanks to intelligent multi-layer wall construction

The acoustic quality of the Mood Line partitions is the result of intensive research and continuous development. The dimensions and the materials used in the partitions' intelligent, multi-layer construction can be adapted to the acoustic requirements of each specific room. This not only means an optimum performance in terms of sound absorption but also Mood Line 55 with magnetic connection makes a great contribution to noise insulation in the workplace.

MOOD LINE 55 mm

Sound absorption coefficient
as per DIN EN ISO 354

125 Hz	as 0,33
250 Hz	as 0,59
500 Hz	as 0,77
1000 Hz	as 0,87
2000 Hz	as 0,94
4000 Hz	as 0,96

Rated sound absorption coefficient

aw 0,80 (H). DIN EN ISO 354 test certificate

MOOD LINE 40 mm

Sound absorption coefficient
as per DIN EN ISO 354

125 Hz	as 0,21
250 Hz	as 0,37
500 Hz	as 0,60
1000 Hz	as 0,69
2000 Hz	as 0,75
4000 Hz	as 0,88

Rated sound absorption coefficient

aw 0,65 (H). DIN EN ISO 354 test certificate