

## PRIME LINE 55/40 - *On-cabinet element*

### Powerful and flexible

Prime Line on-cabinet elements are standard equipped with lateral system rails. Thus, they adapt to the design and function of the partition screens and desk elements and yet are quite independent in terms of versatility and flexibility. Whether in wall thickness 55 mm or 40 mm, positioned on sideboards or on a workbench, they always contribute to a visual and acoustic shielding in the immediate working environment. The elements are equipped with flat covers in anodized aluminium EV1, and alternatively in powder coated anthracite gray RAL 7016 or in white aluminium RAL 9006 as well as with fabric coated profiles.

The on-cabinet elements are available in heights 380, 530 and 680 mm. With each of 7 standard widths, up to 2000 mm and in addition also individually customized, can be responded to any cabinet or desk size and a variety of arrangements.




---

### Data Prime Line 55/40 *On-cabinet element*

Wall thickness 55 mm - alternatively 40 mm

Aluminum frame profile with lateral system rail

Highly sound-absorbing according to  
DIN EN ISO 354

Filler B1 flame retardant according to  
DIN 4102-1

Filler OEKO-TEX Standard 100

Optionally also with an acoustic filling made of pure  
new sheep's wool - 100% sustainable

Fabric covering and decorative surfaces

## Detail view



With organisation rail and organisational accessories height 480 mm



With covering 55 mm without system rail



With covering 40 mm without system rail



Central stand plate with depth 200 mm und width 650

### PRIME LINE 55 mm

Sound absorption coefficient  
as per DIN EN ISO 354

125 Hz	as 0,33
250 Hz	as 0,59
500 Hz	as 0,77
1000 Hz	as 0,87
2000 Hz	as 0,94
4000 Hz	as 0,96

Rated sound absorption coefficient  
aw 0,80 (H). DIN EN ISO 354 test certificate

### PRIME LINE 40 mm

Sound absorption coefficient  
as per DIN EN ISO 354

125 Hz	as 0,21
250 Hz	as 0,37
500 Hz	as 0,60
1000 Hz	as 0,69
2000 Hz	as 0,75
4000 Hz	as 0,88

Rated sound absorption coefficient  
aw 0,65 (H). DIN EN ISO 354 test certificate