

Silence Line - *On-cabinet element 55/40*

Powerful and flexible

Silence Line wall-mounted cupboard units, wall thickness 55 mm or 40 mm, are fitted with a velour finish on both sides as standard. Alternatively, the system can be finished with flat covers. This means they can be customised in design and function to match the partition walls and table elements. With a wall thickness of 40 mm, positioned on sideboards or on a workbench, they always contribute to visual and acoustic screening in the immediate working environment. Available in a variety of fabric collections - divided into 5 price groups - and with over 800 colours, they are a source of inspiration for creative and at the same time highly sound-absorbing room partitioning.

The on-cabinet elements are available in heights 380, 530 and 680 mm. With each of 7 standard widths, up to 2000 mm and in addition also individually customized, can be responded to any cabinet or desk size and a variety of arrangements.



Daten Silence Line

On-cabinet element 55/40

Velcro cover on both sides

Optional with flat cover

Wall thickness 55 mm alternatively 40 mm

Aluminum frame profile optionally
with lateral system rail

Profiles & covers in anodised aluminum EV1,
powder-coated anthracite gray RAL 7016 / white
aluminum RAL 9006

Base plate, powder-coated
Anthracite gray RAL 7016 / white aluminum RAL 9006

Highly sound-absorbing according to DIN EN ISO 354

Filler B1 flame retardant according to DIN 4102-1

Filler Standard 100 by OEKO-TEX®

Fabric covering and decorative surfaces

Optionally with an acoustic filling
made of sheep's wool - 100% sustainable

Detail view



With flat cover
height 680 and 480 mm



Velcro on both sides



Central stand plate with
depth 200 and width 650



Optional with flat cover

Choice of fabric collections Quilting

PG1 Medley **PG2** Cura, Hush, Twist/Twist melange **PG3** Connect, Roccia, King L, Step, Step Melange **PG4** Blazer, Main Line Flax **PG5** Passion

Silence Line 55 mm

Sound absorption coefficient
ap per DIN EN ISO 354

125 Hz	ap 0,33
250 Hz	ap 0,59
500 Hz	ap 0,77
1000 Hz	ap 0,87
2000 Hz	ap 0,94
4000 Hz	ap 0,96

Rated sound absorption coefficient
aw 0,80 (H). DIN EN ISO 354 test certificate

Silence Line 40 mm

Sound absorption coefficient
ap per DIN EN ISO 354

125 Hz	ap 0,21
250 Hz	ap 0,37
500 Hz	ap 0,60
1000 Hz	ap 0,69
2000 Hz	ap 0,75
4000 Hz	ap 0,88

Rated sound absorption coefficient
aw 0,65 (H). DIN EN ISO 354 test certificate